



Elbo Controlli NIKKEN E46CA Tool Presetting Machine

Our range of standard and advanced tool presetting machines are designed, developed and manufactured by our sister company Elbo Controlli NIKKEN.

All Elbo Controlli NIKKEN tool presetters are designed and manufactured 'in-house' at our two sites in Meda near Milan, Italy. Every single construction material and component is carefully controlled and developed specifically with the function and requirement of measuring tools in mind (from the optics and electronics right through to the glass scales, spindles and structural assemblies).



MAIN FRAME & CONSTRUCTION

Machine structure in high quality structural steel to provide increased stiffness with higher accuracy and rigidity. Solid granite column and base (increased substantially in size over previous generation models) to guarantee and maintain maximum accuracy. This construction ensures durability and offers high levels of thermal stability making the E46CA highly suitable for machine shop conditions with no issue of concern in respect of accuracy, repeatability and reproducibility.

SPINDLE SYSTEM

A wide variety of tools can be pre-set utilizing interchangeable spindle cartridges rather than adaptors. This reduces the number of interface connections delivering accuracy across all spindle types. The machine allows for push button electro-mechanical tool clamping of ISO/HSK adaptors and provides storage for up to six additional spindle cartridges in conjunction with an innovative taper contact confirmation system to verify proper tool location. The cartridges supplied for the E46CA all feature our unique spindle identification system (SP-ID) which identifies which spindle is loaded and prohibits selection of the incorrect reference from the library.

FUNCTIONALITY

The software is displayed and interacted with via a 21.5" capacitive touch screen mounted vertically for easy viewing and operation. The screen layout and design is split into two distinct sections. The upper half of the display shows visible images of the current tool and profile whilst the lower section, along with our floating menu window, provides access to all the current functions. Simple icons and graphically driven menus enable the operator to quickly and intuitively manage all tool measurement and inspection modes, in addition a range of auxiliary capabilities are available such as creating CNC Machine origins and tool sets.

SERVICE & SUPPORT

NIKKEN have a UK based service and Engineering team offering unrivalled levels of customer support, we are able to offer a comprehensive range of services including: installation, training, technical support, service and calibration. Our team is 'manufacturer' trained and we stock a wide range of spares to facilitate quick response times and a highly efficient service.



TECHNICAL DATA

Measuring range: diameter max 400 mm (radius 200 mm); max height 600 mm

General Features:

- Base and column in natural granite: max linearity error 8 µm/m
- Steel base with 3 fixed and 1 adjustable feet
- Linear guideways (2 X axis, 1 Z axis) with double recirculating ball bearings slides
- Pneumatic axis movement unlock
- Manual gross movement and manual fine adjustment
- ECN AS371 certified optical scales (resolution 1µm)
- Vertical TFT 21,5" Full HD Touch Screen Monitor
- Keyboard and mouse, plus label printer side support
- Spindles side support (1 for 2 spindles)
- Interchangeable spindle (ISO,BT,CAT, HSK, Polygonal taper, etc.)
- Spindle identification system (SP-ID)
- C axis visualization
- Automatic spindle rotation and electronic index
- Pneumatic spindle brake
- Motorized mechanical tool holder clamping (standard pull stud DIN69872, ISO7388, MAS403)
- Motorized mechanical tool holder clamping (HSK, Polygonal taper)
- Bi-telecentric optical lenses
- Elbo Controlli NIKKEN camera system measuring range (mm) = 10x10 mm
- Monochromatic C-MOS sensor USB 3.0 Super speed connection
- Elbo Controlli NIKKEN camera system resolution = 1 µm
- Elbo Controlli NIKKEN camera system magnification = 25x
- Analogic and digital camera view
- Digital zoom = 4x
- Tool inspection function
- Resizeable camera area
- Embedded ECN operating system Linux based
- ECN machine software C version (yellow screen)
- Number of machine origins / number of tool sets = ∞ / ∞
- Multi-origin function for multitasking machines
- Manual measure function with fixed reticle
- Autotargeting measure function
- Autotargeting measure function with dimension freeze
- Collimation indicators for fixed reticle measure
- On-screen automatic measure of tool corner radius & theoretical centre point
- On-screen automatic measure of tool corner angle & theoretical intersection
- Chamfer measuring function in both Z and X axes
- Adjustable Area of Interest (AOI)
- Automatic spindle rotation and measurement of tool edges
- Adjustable reticles (axis and circles)
- Profile image capture function
- Automatic geometry (multiple geometric entity)
- Geometry by points
- Camera image capture
- DXF files import and comparison with tool
- Manual DXF acquisition of the revolution profile
- Automatic DXF acquisition of the revolution profile
- USB ports (4)
- LAN connection and Wi-Fi connection
- A range of standard post processors

Overall dimensions: L = 1179 mm, H = 1935 mm, D = 568 mm Net weight: ~ 230 kg